

VISCOBASE® 11-570

A Synthetic Base Fluid

A RohMax Product



Function

Lubricating component and base fluid.

Performance

VISCOBASE® 11-570 is suitable for the formulation of semi- and all-synthetic polymer-free high-performance lubricants for the automotive and industrial sector.

VISCOBASE® 11-570 is specially designed for excellent miscibility with mineral oil and synthetic base fluids.

VISCOBASE® 11-570 shows very good solvency towards common oil additives. The typical addition rate depends on the application.

Composition

VISCOBASE® 11-570 is a viscous oligomer derived from alphaolefin and alkyl methacrylate.

Physical Data

Table 1 lists representative physical properties. (These do not constitute specifications.)

VISCOBASE® Series 11 Synthetic Base Fluids

Table 1

Typical Physical Properties of VISCOBASE® 11-570

Visual Appearance	Clear
Color (ASTM D1500)	0.5
Viscosity at 40 °C, mm ² /s (ASTM D445)	2,286
Viscosity at 100 °C, mm ² /s (ASTM D445)	144
Density at 15 °C, g/cm ³ (ASTM D4052)	0.93
Flash Point, °C (ASTM D92)	210

Density

The typical density of VISCOBASE® 11-570, as a function of temperature, is given in Figure 1.

Bulk Viscosity

The bulk handling properties of VISCOBASE® 11-570, as a function of temperature, are provided in Figure 2.

Additional Information

For additional information on product availability, performance data and Material Safety Data Sheets, please contact your RohMax account manager or Customer Service Representative.

For an overview of our entire VISCOPEX® and VISCOBASE® product range and complete information on handling and storage, please visit the Products & Applications section on our website www.rohmax.com.

Figure 1 Density vs. Temperature





Figure 2 Kinematic Viscosity vs. Temperature



This information and all further technical advice is based on our present knowledge and experience. However, they imply no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of the customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

©05/2008 Evonik RohMax Additives GmbH.

VISCOPEX® and VISCOBASE® are registered trademarks of Evonik RohMax Additives GmbH

Europe, Africa, Mideast:

Evonik RohMax Additives GmbH • Kirschenallee • 64293 Darmstadt • Germany • TEL: +49 61511809

Americas:

Evonik RohMax USA, Inc. • 723 Electronic Drive • Horsham, Pennsylvania 19044-2228 • TEL: +1 215 706 5800 • TOLL-FREE: 1 888 876 4629

Asia Pacific:

Evonik RohMax Asia Pacific Pte. Ltd. • 3 International Business Park 07-18 Nordic European Centre • Singapore 609927 • TEL: +65 6899 0080

info-rohmax@evonik.com • www.rohmax.com

